



Fully mounted reversible On-land /in furrow plough

Agrolux ploughs are developed for farmers and contractors who focus on professional farming. Agrolux ploughs have unique design and features that makes them reliable and economical over time.

The new XRWT OL is available from 5 up to 7 furrows and equipped with hydraulic adjustable furrow width.





XRWT OL is easy to turn over because of favorable geometry.

Agrolux XRWT OL

The new model of Agrolux plough is based on the well proven XRWT. The main difference is the front end. XRWT OL has a new stronger headstock and turnover arm as it is available also as a seven furrow version.

- Rear mounted depth and transport wheel for best weight transfer and depth control. New stronger wheel arm mounted outside gives more space for residues.
- Designed for wide tractors, up to four meter fully on land.
- Easy to change between on land and in furrow ploughing.
- Separate alignment when ploughing in furrow. Saves time as the plough works like a standard plough and do not needs to go out to on land position for reversing.



Combi wheel for roadwork.

Technical specification

Model	Number of furrows	Working width cm	Weight kg	Point to point clearance cm	Under beam clearance cm	Max. effect hp	Approx. lift requirement kg
XRWT OL 5975*	5	150-275	2520	90	75/80	350	6500
XRWT OL 6975*	6	180-330	2820	90	75/80	350	8500
XRWT OL 7975	7	210-385	3120	90	75/80	350	11000

X=Classification R=Reversible W= Hydraulically adjustable working width T= Tripped OL= Onland

*= Models can be rebuild with one extra furrow



XRWT OL in onland position.



XRWT OL in furrow position.



101002323 AGROLUX/GB/XRWT_OL/BRO/1013



Agrolux
S-590 96 Överum
Tlf. +46 493 361 00
Fax +46 493 308 00
www.agrolux-ploughs.com

Subject to be changed without notice.